



SATURN SD230 inflatable boat is a smallest dinghies available with high-pressure inflatable air floor.

SD230 inflatable boat is lightweight, does not take much space and can be carried by one person. This model of inflatable dinghy will take up to 2.5 HP short shaft outboard motor, and can carry up to 1-2 people comfortably or 3 people maximum. SD230 also great with small electric trolling motor as an economical alternative.

SD230 SATURN inflatable boat is excellent as a small rowing dinghy. You can easily reach your sailboat or go for the day of fishing on a lake. SD230 moves nice and easy when rowing, and due to the high stability of inflatable boat, it is possible to stand up for fly fishing or while boarding your yacht.

Double layers of fabric at the bottom of the tubes and rub-strike protector along the keel provide extra protection from sharp rocks and abrasive sand. The safety valve will prevent excessive air pressure in the boats chambers.



SATURN SD230 FEATURES:

- All around rope grab line.
- Separate internal air chambers.
- One-way drain valve with plug.
- All around, durable rubber strike.
- Safety valve to prevent over inflation.
- Stainless steel D-rings for easy towing.
- Reliable flat air valves with pushpin design.
- Front bow D-ring with integral lifting handle.
- Spare rope for attaching anchor is included.
- Double layer of fabric at the bottom of tubes.
- High-pressure drop stitch air floor is included.
- Deep inflatable V-keel with a rub strike protector.
- Extremely rigid, lightweight hull for excellent performance.
- Lightweight and strong removable aluminum seat benches.
- Heavy-duty marine grade plywood transom for outboard motor.
- Equipment: aluminum oars, repair kit, seat bench and carry bag.
- Free, complimentary generic high-volume hand pump is included.

New features further improve inflatable boats durability and practicality:

- Air valves have been moved toward the inside of boat's tubes and away from direct exposure to the elements. This will allow easier inflation from inside the boat and will minimize damage caused by sun and rain while the boat is stored uncovered for prolonged periods of time. Rain water will not accumulate inside the valves.
- Triangular symmetrical splash guards were installed on the transom corners to provide the sensitive transom of an uncovered boat with additional protection and shade from the elements throughout extended periods in Tropical environments.



Tech Specs*

Overall Length	7.6'
Inside Length	4.7'
Overall Width	4.5'
Inside Width	2.1'
Tube Diameter	16.5"
Chambers	3+1+1
Person Capacity	2+1
Loading Capacity	441 lbs
Max Motor Power	2.5 HP (15" shaft / 50 lbs)
Tube Weight	66 lbs
Shipping Size	41 x 24 x 12"
Shipping Weight	70 lbs
Floor Type	Drop Stitch Air Floor
Material	1100 Denier Reinforced PVC
Seams	Quadruple Overlap
Air Valves	Recessed One-Way
Speed (approx.)	10 mph (2.5HP w/1 adult)



Order On-line at www.BoatsToGo.com TOLL FREE 1-866-299-7740 M-F 10-6 ET