



8.6' SD260 Saturn Inflatable Boat

The 8'6" SATURN SD260 inflatable boat is one of the smallest dinghies available with a high pressure air floor. A reliable tender is about the most important piece of equipment that a cruiser can own. The SD260 is great as a tender for yachts or sailboats. This inflatable boat is lightweight and does not take up much space once deflated. SD260 boats can take up to a 10 HP short shaft outboard motor and can carry up to 3 people maximum. This boat can also be used as a lifesaving raft in case of an emergency.

The Saturn SD260 inflatable boat comes standard with a high-pressure drop stitch air deck floor. Our drop stitch floors can take up to 9 psi of air pressure, and become extremely rigid once properly inflated. Not only do air floors make inflatable boats much lighter and more compact when deflated, but they also make it much easier to assemble and disassemble the boat. You simply unroll it and pump in air with the included hand pump. To deflate the boat, simply open all air valves and start rolling the boat from the transom, or quickly suck all air out with an electric pump. Double layers of fabric at the bottom of the tubes and rub-strake protector along the keel provide extra protection from sharp rocks and abrasive sand. The safety valve will prevent excessive air pressure in the boats chambers.



SATURN SD260 FEATURES:

- All around rope grab line.
- Separate internal air chambers.
- One-way drain valve with plug.
- All around, durable rubber strike.
- Safety valve to prevent over inflation.
- Stainless steel D-rings for easy towing.
- Reliable flat air valves with pushpin design.
- Front bow D-ring with integral lifting handle.
- Spare rope for attaching anchor is included.
- Double layer of fabric at the bottom of tubes.
- High-pressure drop stitch air floor is included.
- Deep inflatable V-keel with a rub strake protector.
- Extremely rigid, lightweight hull for excellent performance.
- Lightweight and strong removable aluminum seat benches.
- Heavy-duty marine grade plywood transom for outboard motor.
- Equipment: aluminum oars, repair kit, seat bench and carry bag.
- Free, complimentary generic high-volume hand pump is included.

New features further improve inflatable boats durability and practicality:

- Air valves have been moved toward the inside of boat's tubes and away from direct exposure to the elements. This will allow easier inflation from inside the boat and will minimize damage caused by sun and rain while the boat is stored uncovered for prolonged periods of time. Rain water will not accumulate inside the valves.
- Triangular symmetrical splash guards were installed on the transom corners to provide the sensitive transom of an uncovered boat with additional protection and shade from the elements throughout extended periods in Tropical environments.

Tech Specs*

Overall Length	8.6'
Inside Length	5.0'
Overall Width	5.4'
Inside Width	2.4'
Tube Diameter	16.5"
Chambers	3+1+1
Person Capacity	3
Loading Capacity	772 lbs
Max Motor Power	8 HP (15" shaft / 80 lbs)
Tube Weight	75 lbs
Shipping Size	41 x 24 x 12"
Shipping Weight	85 lbs
Floor Type	Drop Stitch Air Floor
Material	1100 Denier Reinforced PVC
Seams	Quadruple Overlap
Air Valves	Recessed One-Way
Speed (approx.)	10 mph (6HP w/2 adults)

SD260



Order On-line at www.BoatsToGo.com TOLL FREE 1-866-299-7740 M-F 10-6 ET