



Secure the backrest straps to the grommets using the same method as for the D-rings. For easy removal, use optional carabiners to quickly attach or detach them. Adjust the backrest angle by pulling the loose strap end. The backrest remains semi-soft for added comfort.

TIP: use optional carabiners

Connect the two short straps with buckles to the two middle D-rings at the front and rear.

Connect the two short straps with buckles to the two middle D-rings at the front and rear.

Connect four long straps to 4 outer D-rings

Connect four long straps to 4 outer D-rings



Attach the straps to the D-rings using the same method as the backrest, securing them with plastic sliders.



Position the Platform – Place the platform over two inflatable paddle boards set side by side to form a catamaran structure.
Arrange the Straps – Run four long straps underneath each paddle board’s hull, ensuring they lay flat against the bottom.
Secure the Straps – Connect each long strap to a short strap with a buckle.
Tighten the Straps – Pull the free end of each strap firmly through the buckle to tighten it completely. For added tension, step onto the platform while pulling.
Avoid Over-Tightening – Do not overtighten, as excessive force may damage the plastic slider.

Mount the Trolling Motor – Secure the electric trolling motor to the transom at the rear of the platform.
Wire the Motor to the Battery – Run the motor’s power cables neatly along the platform to connect with a 12V deep-cycle battery.
Position the Battery – Place the battery either at the front or rear of the platform, resting on one of the paddle boards.
Install Tracking Fins – Attach fins to the bottom of each paddle board to improve directional stability and tracking, enhancing maneuverability.

Safety Warning: Always carry personal flotation devices and an emergency whistle. Do not install a gas outboard motor.