

always with you... Achilles



ACHILLES CORPORATION

Rubberized Fabric & Marine Sales Department
 Head office : Shinjuku Front Tower 22F, 2-21-1 Kitashinjuku,
 Shinjuku-ku, Tokyo 169-8885
 Tel : 81-3-5338-9363 Fax : 81-3-5338-9369

Apr-2016

DESIGN VALUE

T10 Series

SUPPORT FABRIC	Type	Polyester
	Yarn	1100dtex
	Contexture(/cm)	wp×wf 10×10
COATING	outside coating	Chlorosulfonated Polyethylene (CSM)
	inside coating	Chloroprene (CR)
THICKNESS		mm	0.84±0.10
WIDTH		mm	1500 -0, +20
WEIGHT		g/m ²	1250

PHYSICAL PROPERTY

T10 Series

	(STANDARDS)	(UNITS)	
Tensile strength	ISO 1421		warp 401
		daN/5cm	weft 366
Tear Resistance	ISO 4674-1		warp 34
	trouser-shaped	daN	weft 26
Adhesion	ISO 2411	daN/2.5cm	>4
Low-temperature resistance	ISO 4675		
	bend test	°C	-30°C pass
UV Long-Life Carbon Arc Lamp		1000h	CSM None crack

The value is measurement, not guarantee.